



## EL TRUCK 2.5 TON



Counterbalanced Electric Truck  
4-wheels 80 Volts  
3.5" Color Display  
Foot parking brake  
Rear Handle with Horn

Pictures may differ from the quoted configuration. Baoli Datasheet is an integral part of the offer.

### Type

Basic truck	KBE 25 G1
Tyres	Superelastic
Truck version	Lead-acid version ambient temperature (-20 to +40 degrees)
PRE-configured truck	PRE-13: KBE 25 G1; CE; VFHM 4650; Hang on sideshift; Forks 1200 mm; 80V 3 PzS 450 Ah; Load backrest; Superelastic tyres; Comfort seat + ISO safety valve 3691; Auxiliary hydraulics double for VFHM; Full cabin; Roof screen made of polycarbonate; USB; Hydraulic controls multi-lever (4 levers); Flashing beacon beneath roof, protected; LED Working spotlight rear; LED Lighting system; LED Working spotlight front; Acoustic signalling device; Speed reduction with raised fork carriage (500 mm); Curve speed reduction; 2 exterior mirrors; Water top-up system; 20l tank; NO charger
KION Cost Carrier	609103000000B072
Material number	60910000003

### Mast

Mast	VFHM 4650 h1=2173 h2=1535 h4=5289
Fork carriage	6 rollers 1040 mm wide, ISO 2A
Fork arms	Length 1200 mm, cross section 100x45 mm, ISO 2A
Auxiliary hydraulics	double for VFHM mast
Hydraulic controls	Multi-lever operation, 4 individual levers for lifting, tilting and auxiliary hydraulics on right beside seat
Load backrest	Type A 1000 mm high for fork carriage 1040 mm
Hydraulic system	Multi-grade universal hydraulic oil for temperatures of -20/+40 degrees



## Cabin area

Driver's seat	Comfort seat + ISO safety valve 3691
Cabin	Full cabin with cabin doors including damping of left cabin door windscreen and rear window, wiper/washer system front and rear, heated rear window. Roof screen according to specification. Entry grip front left (battery change possible with specialist tools)
Roof screen	Roof screen made of polycarbonate: closed overhead guard with optimised upward visibility
Electrical equipment	USB Charger
Rearview mirrors	2 exterior mirrors

## Specification

Warning light	Flashing beacon beneath roof, protected
Working spotlight rear	LED version on overhead guard top right, protected
Lighting system	LED version front: 2 protected LED headlights with drive direction indicator rear: LED tail and stop lights, drive direction indicators hazard warning lights
Working spotlight front	LED on overhead guard top left and right, protected
Warning device	Acoustic signalling device
Drive control	Speed reduction with raised fork carriage (500 mm)
Speed assist	The steering angle controlled speed limiter reduces the breakage of goods by ensuring a suitable curve speed.

## Battery

Battery	80V 3 PzS 450 Ah
Autofiller	for 80 V battery
Water top up kit	20l tank

## Attachment

Sideshift	Hang on sideshift 2,5t 1040mm
-----------	-------------------------------