



## EL TRUCK 3.5 TON



Counterbalanced Electric Truck  
4-wheels 80 Volts  
3,5" Color Display  
Foot parking brake  
Rear Handle with Horn

Pictures may differ from the quoted configuration. Baoli Datasheet is an integral part of the offer.

### Type

|                      |  |
|----------------------|--|
| Basic truck          | KBE 35 G1  |
| Tyres                | Superelastic 225/75-15/6.5-10  |
| Truck version        | Lead-acid version ambient temperature (-20 to +40 degrees)   |
| PRE-configured truck | PRE-5: KBE 35 G1; CE; VFHM 4650; Hang on sideshift; Forks 1200 mm; 80V 3 PzS 600 Ah; Load backrest; Superelastic tyres; Comfort seat + ISO safety valve 3691; Auxiliary hydraulics double for VFHM; Full cabin; Roof screen made of polycarbonate; Heating; USB; Hydraulic controls multi-lever (4 levers); Flashing beacon beneath roof, protected; LED Working spotlight rear; LED Lighting system; LED Working spotlight front; Acoustic signalling device; Speed reduction with raised fork carriage (500 mm); 2 exterior mirrors; Water top-up system; 20l tank; NO charger |
| KION Cost Carrier    | 609202000000B076   |
| Material number      | 60920000002  |

### Mast

|                      |   |
|----------------------|---|
| Mast                 | VFHM 4650 h1=2212 h2=1453 h4=5552   |
| Fork carriage        | 6 rollers 1100 mm wide, ISO 3A  |
| Fork arms            | Length 1200 mm, cross section 150x50 mm, ISO 3A   |
| Auxiliary hydraulics | double for VFHM mast  |
| Hydraulic controls   | Multi-lever operation, 4 individual levers for lifting, tilting and auxiliary hydraulics on right beside seat |
| Load backrest        | Type A 1000 mm high for fork carriage 1040 mm   |
| Hydraulic system     | Multi-grade universal hydraulic oil for temperatures of -20/+40 degrees                                       |



---

## Cabin area

|                      |  |
|----------------------|--|
| Driver's seat        | Comfort seat + ISO safety valve 3691   |
| Cabin                | Full cabin with cabin doors including damping of left cabin door windscreen and rear window, wiper/washer system front and rear, heated rear window. Roof screen according to specification. Entry grip front left (battery change possible with specialist tools) |
| Roof screen          | Roof screen made of polycarbonate: closed overhead guard with optimised upward visibility  |
| Heating              | Powerful 1000 W electric heater. Effective heating of cabin and foot well.   |
| Electrical equipment | USB Charger  |
| Rearview mirrors     | 2 exterior mirrors   |

---

## Specification

|                         |   |
|-------------------------|---|
| Warning light           | Flashing beacon beneath roof, protected   |
| Working spotlight rear  | LED version on overhead guard top right, protected  |
| Lighting system         | LED version front: 2 protected LED headlights with drive direction indicator rear: LED tail and stop lights, drive direction indicators hazard warning lights |
| Working spotlight front | LED on overhead guard top left and right, protected   |
| Warning device          | Acoustic signalling device  |
| Drive control           | Speed reduction with raised fork carriage (500 mm)  |

---

## Battery

|                  |                  |
|------------------|------------------|
| Battery          | 80V 3 PzS 600 Ah |
| Autofiller       | for 80 V battery |
| Water top up kit | 20l tank         |

---

## Attachment

|           |                                 |
|-----------|---------------------------------|
| Sideshift | Hang on sideshift 3-3,5t 1100mm |
|-----------|---------------------------------|