

3-HJULET EL TRUCK 2.0 TON - LITHIUM

1 / KBE/T 15-20 BM 609001

Counterbalanced Electric Truck

4-wheels 80 Volts 3,5" Color Display Foot parking brake Rear Handle with Horn

Type

 KION Cost Carrier
 609001000100B043

 Material number
 6090000001

 Basic truck
 KBET 20 Li G1

 Tyres
 Superelastic

Truck version Li-Ion version ambient temperature

PRE-configured truck PRE-L201: KBET 20 Li G1; CE; VFHM 4700; Hang on sideshift; Li-ion battery 80 V 228 Ah; Load

backrest; Forks 1200mm; Superelastic tyres; Comfort seat + ISO valve; double hydraulics; Standard oil; Standard OHG cabin can be retrofitted; USB Charger; Multi-lever (4 levers); Flashing beacon; working spotlight rear; LED lights; working spotligh front; Acoustic signalling device; Speed red.w.raised FC; Curve

speed reduction; Panoramic rearview mirror

Mast

Mast VFHM 4700 h1=2191 h2=1140 h4=5740

Fork carriage 6 rollers 1040 mm wide, ISO 2A

Load backrest Type A 1000 mm high for fork carriage 1040 mm

Fork arms 1200mm, 80x40mm, 2A Auxiliary hydraulics double for VFHM mast

Hydraulic controls Multi-lever operation, 4 individual levers for lifting, tilting and auxiliary hydraulics on right beside seat

Hydraulic system Multi-grade universal hydraulic oil for temperatures of -20/+40 degrees

Cabin area

Driver's seat Comfort seat + ISO safety valve 3691

Cabin Steel overhead guard open on all sides, entry grip front left, handle rear right cabin can be retrofitted

Electrical equipment USB Charger

Rearview mirrors Panoramic rearview mirror

Specification

Warning light Flashing beacon beneath roof, protected

Working spotlight rear LED version on overhead guard top right, protected

Lighting system LED version front: 2 protected LED headlights with drive direction indicator rear: LED tail and stop lights,

drive direction indicators hazard warning lights

Working spotlight front LED on overhead guard top left and right, protected

Warning device Acoustic signalling device

Drive control Speed reduction with raised fork carriage (500 mm)

Speed assist The steering angle controlled speed limiter reduces the breakage of goods by ensuring a suitable curve

speed.



Battery

Battery Li-ion battery 80 V 228 Ah

Attachment

Sideshift Hang on sideshift 609001