



## GAS TRUCK 2.5 TON



Pictures may differ from the quoted configuration. Baoli Datasheet is an integral part of the offer.

### Type

Basic truck	KBG 25 G1 (EU5 HDI)
Tyres	Superelastic 225/75-10 / 180/70-8
PRE-configured truck	PRE-G252: KBG 25 G1; HDI EU5; CE; VFHM 4650; Forks 1200mm; Load backrest; Hang on sideshift; Superelastic tyres; Comfort seat + ISO valve; Auxiliary hydraulics double for VFHM; Full cabin; Heater; USB; Vertical exhaust; Flashing beacon beneath roof, protected; LED Working spotlight rear; LED Lighting system; LED Working spotlight front; Acoustic signalling device; 2 exterior mirrors
Fuel system	Holder gas bottle
Drive unit	HDI LPG P24 / 2,4l / 40,2kW EU5
KION Cost Carrier	601003000300B081
Material number	60100000003

### Mast

Mast	VFHM 4650 h1=2212 h2=1453 h3=4650h4=5402
Fork carriage	6 rollers 1040 mm wide, ISO 2A
Load backrest	Type A 1000 mm high for fork carriage 1040 mm
Fork arms	Length 1200 mm, cross section 100x45 mm, ISO 2A
Auxiliary hydraulics	double for VFHM mast
Hydraulic controls	Multi-lever operation, 4 individual levers for lifting, tilting and auxiliary hydraulics on right beside seat
Hydraulic system	Multi-grade universal hydraulic oil for temperatures of -20/+40 degrees



---

### Cabin area

Driver's seat	Comfort seat + ISO safety valve 3691
Cabin	Full cabin with cabin doors including damping of left cabin door windscreen and rear window, wiper/washer system front and rear, heated rear window. Roof screen according to specification. Entry grip front left
Heating	Heater
Rearview mirrors	2 exterior mirrors
Roof screen	Glass
Electrical equipment	USB Charger

---

### Specification

Warning light	Flashing beacon beneath roof, protected
Lighting system	LED version front: 2 protected LED headlights with drive direction indicator rear: LED tail and stop lights, drive direction indicators hazard warning lights
Warning device	Acoustic signalling device
Exhaust system	Exhaust upwards
Air filter	Standard air filter
Working spotlight rear	LED version on overhead guard top right, protected
Working spotlight front	LED on overhead guard top left and right, protected

---

### Attachment

Sideshift	Hang on sideshift 2,5t 1040mm
-----------	-------------------------------